



Data Sheet  
**OMM 335PM**

*Distributed by*



[www. BristolInstruments.com](http://www.BristolInstruments.com)

Bristol Instruments  
90 Canal Street, 4th Floor  
Boston, MA 02114

Toll free  
877-866-8500



## OMM 335PM



OMM 335PM is a 4-digit process monitor.

The instrument is based on a microcontroller and an A/D converter, which ensures good accuracy and easy operation of the instrument.

The 22 mm cross-section of the circular instrument body allows its convenient mounting into mosaic and signalling panels.

### PROCESS MONITOR

- 4-digit programmable projection
- Range:  $\pm 5 \text{ mA}/\pm 20 \text{ mA}/4\dots 20 \text{ mA}$   
 $\pm 2 \text{ V}/\pm 5 \text{ V}/\pm 10 \text{ V}$
- Digital filters, Linearization
- Size of DIN 51,5 x 29,5 mm
- Power supply 10...30 V DC/24 VAC

**OMM 335PM**  
PROCESS MONITOR

### OPERATION

The instrument is set and controlled by two buttons located on its the body.

Standard equipment is the OM Link USB interface, which, when using the control program, allows you to edit and archive all device settings and to update firmware.

All settings are stored in FLASH memory (they hold even after the power is turned off).

### STANDARD FUNCTIONS

#### PROGRAMMABLE PROJECTION

**Selection:** of input type and measuring range

**Setting:** manual, optional projection on the display may be set in menu for both limit values of the input signal, e.g. input  $0\dots 10 \text{ V} > 0\dots 150,0$

**Projection:** -999...9999

#### FUNCTIONS

**Linearization:** non-linear signals can be linearized by the means of a linearization table (up to 50 points)

## TECHNICAL DATA

### INPUT

Number of inputs	1		
<b>PM</b> Range	optional in configuration menu		
	±5 mA	< 200 mV	Input I
	±20 mA	< 200 mV	Input I
	4...20 mA	< 200 mV	Input I
	±2 V	1 MΩ	Input U
	±5 V	1 MΩ	Input U
	±10 V	1 MΩ	Input U

### PROJECTION

**Display:** -999...9999, single color 7-segment LED  
**Digit height:** 14 mm  
**Display color:** red or green  
**Decimal point:** adjustable - in menu  
**Brightness:** adjustable

### INSTRUMENT ACCURACY

**TC:** 50 ppm/°C  
**Accuracy:** ±0,15% of range + 1 digit (for projection -999...1999)  
**Rate:** 0,5...100 measurement/s  
**Overload capacity:** 2x; 10x (t < 30 ms)  
**Linearization:** linear interpolation in 50 points (only via OM Link) (only via OM Link)  
**OM Link:** company communication interface for operation, setting and update of instruments  
**Watch-dog:** reset after 500 ms  
**Calibration:** at 25°C and 40 % r.h.

### POWER SUPPLY

**Range:** 24 V DC/AC, ±10 %, PF ≥ 0,4, I<sub>STP</sub> < 45 A/1,1 ms  
 10...30 VDC/24 VAC, ±10 %, PF ≥ 0,4, I<sub>STP</sub> < 45 A/1,1 ms, isolated  
**Consumption:** < 0,2 W/0,2 VA

### MECHANIC PROPERTIES


**Material:** PA66, incombustible UL 94 V-1  
**Dimensions:** 51,5 x 29,5 x 66 mm (w x h x d)  
**Panel cutout:** Ø 22,5 mm

### OPERATING CONDITIONS

**Connection:** connector terminal blocks, section < 1,3 mm<sup>2</sup>  
**Stabilization period:** within 5 minutes after switch-on  
**Working temperature:** -20°...60°C  
**Storage temperature:** -20°...85°C  
**Protection:** IP65 (front panel only)  
**El. safety:** EN 61010-1, A2  
**Dielectric strength:** 700 VAC per 1 min test between supply and input  
**Insulation resistance:** for pollution degree II, measuring cat. II, power supply > 250 V (PI)  
**EMC:** EN 61326-1

PI - Primary insulation, DI - Double insulation

## CONNECTION



- 5 **GND**
- 4 **Input I**
- 3 **Input U**
- 2 **Power**

## ORDER CODE

**OMM 335PM** -  -

<b>Power supply</b>	10...30 V AC/DC	<b>0</b>	
	24 V AC/DC	<b>2</b>	
<b>Display color</b>	red		<b>1</b>
	green		<b>2</b>
<b>Specification</b>	customized version, do not fill in		<b>00</b>

Basic configuration of the instrument is indicated in bold.