

Data Sheet
OM 602UQC

Distributed by



[www. BristolInstruments.com](http://www.BristolInstruments.com)

Bristol Instruments
90 Canal Street - 4th Floor
Boston, MA 02114

Toll free
877-866-8500



UNIVERSAL TWO-CHANNEL COUNTER

- 6-DIGIT PROGRAMMABLE PROJECTION
- COUNTER/FREQUENCY/CLOCK/TIMER
- 0,002 Hz...1 MHz; UP/DW COUNTER, IRC
- MAT. FUNCTIONS, DIGIT. FILTER, TARE, PRESET, SUM
- SIZE OF DIN 96 x 48 MM
- POWER SUPPLY 10...30 V AC/DC; 80...250 V AC/DC
- Option
 - Comparators • Data output • Analog output
 - Measuring data record

OM 602UQC



OM 602UQC is a universal 6-digit panel programmable two-channel impulse counter/frequency meter/evaluation of signals from IRC sensors and timer/clock.

The instrument is based on a single-chip microprocessor and a powerful programmable gate array, which guarantees high accuracy, stability and easy control.

OM 602UQC

UNIVERSAL TWO-CHANNEL COUNTER

OPERATION

The instrument is set and controlled by five buttons located on the front panel. All programmable settings of the instrument may be performed in three adjusting modes:

LIGHT MENU is protected by optional number code and contains solely items necessary for instrument setting.

PROFI MENU is protected by optional number code and contains complete instrument setting.

USER MENU may contain arbitrary items from the programming menu (LIGHT/PROFI), which determine the right (see, change). Access w/o password.

Standard equipment is the OM Link interface, which together with operation program enables modification and filing of all instrument settings as well as performing firmware updates (with OML cable). The program is also designed for visualization and filing of measured values from more instruments.

All settings are stored in the EEPROM memory (settings hold even after the instrument is switched off). The measured units may be projected on the display.

OPTION

COMPARATORS are assigned to monitor one, two, three or four limit values with relay output. As a user you can select the mode limit: LIMIT/BATCH/FROM-TO. The limits have adjustable hysteresis within the full range of the display as well as selectable delay of the switch-on in the range of 0...99,9 s. Reaching the preset limits is signalled by LED and simultaneously by the switch-on of the relevant relay.

DATA OUTPUTS are for their rate and accuracy suitable for transmission of the measured data for further projection or directly into the control systems. We offer an isolated RS232 and RS485 with the ASCII/PROFIBUS protocols.

ANALOG OUTPUTS will find their place in applications where further evaluating or processing of measured data is required in external devices. We offer universal analog output with the option of selection of the type of output - voltage/current. The value of analog output corresponds with the displayed data. Its type and range are selectable in menu.

MEASURING DATA RECORD is an internal time control of data collection. It is suitable where it is necessary to register measured values. Data record is governed via RTC with data storage in a selected time segment and cycle. Up to 266 000 values may be stored in the instrument memory. Data transmission into PC via serial interface RS232/485 and OM Link.

STANDARD FUNCTIONS

PROGRAMMABLE PROJECTION

Input: NPN, PNP, on contact, IRC, line

Measur. modes: counter/frequency meter/UP-DW counter + frequency/counter for IRC + frequency

Calibration: calibration coefficient for each channel may be set in menu independently

Projection: -99999...999999 with stable or floating DT in format 10/24/60

Measur. channels: A and B, from one or more measuring inputs two independent functions may be evaluated

Time base: 0,05/0,5/1/2/5/10/20 s /1/2/5/10/15 min

EXCITATION

Range: 5...24 VDC/1,2 W, for feeding sensors and transmitters

FUNCTIONS

Linearization: linear interpolation in 50 points (only via OM Link)

Tare: designed to reset display upon non-zero input signal

Min./max. value: registration of min./max. value reached during measurement

Peak value: the display shows only max. or min. value

Mathemat. operations: polynom at the same time between inputs - sum, difference, product, quotient, absolute value

Preset: initial nonzero value that is always read after resetting the device

Current value: one-off setting of the initial value

Summation: registration of figures upon shift operation

Time backup: time is running even when the power supply is turned off (the display is off)

DIGITAL FILTERS

Input filter: transmits input signal up to 1 MHz...10 min

Floating/Exp./Arithm. average: from 2...30/100/100 measurements

Rounding: setting the projection step for display

EXTERNAL CONTROL

Lock: control keys blocking

Hold: display/instrument blocking

Tare: tare activation

Resetting MM: resetting min./max. value, counter resetting

Start/Stop: timer/clock control

